

Regal Castors[®]
The Feel of Smoothness

B-F/20, Saraf Kaskar Industrial Estate, S.V. Road, Oshiwara, Jogeshwari (W), Mumbai-400 102, India.
 Telefax: 0091-22-26790437, 66951178.
 Website: www.regalcastors.com Email: sales@regalcastors.com





E-CATALOGUE

A. CASTORS WHEELS

SR.NO.	PRODUCT NAME	PRODUCT CODE	IMAGES	SPECIFICATIONS
65 MM WHEEL DIAMETERS:				
1	POLY65A	PU65A		<p>(A) Static Loading Capacity - 65 kgs per Castor. (B) Wheel Diameter - 65 mm. (C) Unhooded Castor, Material - High Impact Nylon Core with Soft Grey/Black PU tread on Wheel. (D) Various sized Stems (Mountings) can also be made as per requirements. (E) Castors can be made in any colour combination required.</p> <p>BENEFITS: Provides sufficient traction. Squeak-free, Scratch-resist, Ideal for modern floorings. QUALITY TEST: Passed as per International Standards (ANSI, BIFMA, DIN, EN etc.). OEM's are welcome.</p>
60 MM WHEEL DIAMETERS:				
2	POLY60B	PU60B		<p>(A) Static Loading Capacity - 60 kgs per Castor. (B) Wheel Diameter - 60 mm. (C) Unhooded Castor, Material - High Impact Nylon Core with Soft Grey/Black PU tread on Wheel. (D) Various sized Stems (Mountings) can also be made as per requirements. (E) Castors can be made in any colour combination required.</p> <p>BENEFITS: Provides sufficient traction. Squeak-free, Scratch-resist, Ideal for modern floorings. QUALITY TEST: Passed as per International Standards (ANSI, BIFMA, DIN, EN etc.). OEM's are welcome.</p>

3	POLY60A	PU60A		<p>(A) Static Loading Capacity - 60 kgs per Castor. (B) Wheel Diameter - 60 mm. (C) Unhooded Castor, Material - High Impact Nylon Core with Soft Grey/Black PU tread on Wheel. (D) Various sized Stems (Mountings) can also be made as per requirements. (E) Castors can be made in any colour combination required.</p>	<p>BENEFITS: Provides sufficient traction. Squeak-free, Scratch-resist, Ideal for modern floorings. QUALITY TEST: Passed as per International Standards (ANSI, BIFMA, DIN, EN etc.). OEM's are welcome.</p>
4	SLEEK60	SL60		<p>60 mm Wheel Dia Nylon Castor.</p>	<p>QUALITY TEST: Passed as per International Standards (ANSI, BIFMA, DIN, EN etc.). OEM's are welcome.</p>
50 MM WHEEL DIAMETERS:					
5	POLY50	PU50		<p>(A) Static Loading Capacity - 55 kgs per Castor. (B) Wheel Diameter - 50 mm. (C) Castor Material - High Impact Nylon Core with Soft Grey/Black PU tread on Wheel. (D) Various sized Stems (Mountings) can also be made as per requirements. (E) Castors can be made in any colour combination required.</p>	<p>BENEFITS: Provides sufficient traction. Squeak-free, Scratch-resist, Ideal for modern floorings. QUALITY TEST: Passed as per International Standards (ANSI, BIFMA, DIN, EN etc.). OEM's are welcome.</p>
6	ELEGANT 02	EL02		<p>(A) Static Loading Capacity-50 kgs per Castor. (B) Wheel Diameter-50 mm. (C) Hub Dia 40 mm (D) Castor Material-Nylon 6 (Also, available in Co-polymer & Glass reinforced Nylon). (E) Various sized Stems (Mountings) can also be made as per requirements. (F) Castors can be made in any colour required.</p>	<p>QUALITY TEST: Passed as per International Standards (ANSI, BIFMA, DIN, EN etc.). OEM's are welcome.</p>



7	MATT CLASSIC	MT-CL		<p>(A) Static Loading Capacity - 50 kgs per Castor. (B) Wheel Diameter - 50 mm (C) Hub Dia 16 mm. (D) Castor Material - Nylon 6 (Also, available in Virgin PP on customers' demand). (E) Various sized Stems (Mountings) can also be made as per requirements. (F) Castors can be made in any colour required.</p>	<p>QUALITY TEST: Passed as per International Standards (ANSI, BIFMA, DIN, EN etc.). OEM's are welcome.</p>
8	TREND	TD		<p>(A) Static Loading Capacity - 50 kgs per Castor. (B) Wheel Diameter - 50 mm. (C) Castor Material - Nylon 6 (Also, available in Co-Polymer PP on Customers' demand). (D) Riveted Wheels for extra load bearing capacity. (E) Various sized Stems (Mountings) can also be made as per requirements. (F) Castors can be made in any colour combination required.</p>	<p>QUALITY TEST: Passed as per International Standards (ANSI, BIFMA, DIN, EN etc.). OEM's are welcome.</p>
9	ELEGANT 01	EL01		<p>(A) Static Loading Capacity-50 kgs per Castor. (B) Wheel Diameter-50 mm. (C) Hub Dia 32 mm. (D) Castor Material-Nylon 6 (Also, available in Co-polymer & Glass reinforced Nylon). (E) Various sized Stems (Mountings) can also be made as per requirements. (F) Castors can be made in any colour required.</p>	<p>QUALITY TEST: Passed as per International Standards (ANSI, BIFMA, DIN, EN etc.). OEM's are welcome.</p>
10	ELEGANT	EL		<p>(A) Static Loading Capacity - 75 kgs per Castor. (B) Wheel Diameter - 50 mm. (C) Hub Dia 40 mm. (D) Castor Material - Glass reinforced Nylon. (E) Riveted Wheels for extra load bearing capacity. (F) Various sized Stems (Mountings) can also be made as per requirements. (G) Castors can be made in any colour required.</p>	<p>QUALITY TEST: Passed as per International Standards (ANSI, BIFMA, DIN, EN etc.). OEM's are welcome.</p>
11	EXCLUSIVE	EX		<p>(A) Static Loading Capacity - 50 kgs per Castor. (B) Wheel Diameter - 50 mm. (C) Castor Material - High Impact Nylon. (Also available in Co-Polymer PP on Customers' demand. (D) Various sized Stems (Mountings) can also be made as per requirements. (E) Castors can be made in any colour required.</p>	<p>QUALITY TEST: Passed as per International Standards (ANSI, BIFMA, DIN, EN etc.). OEM's are welcome.</p>

12	EZEE	EZ		<p>(A) Static Loading Capacity - 45 kgs per Castor. (B) Wheel Diameter - 50 mm. (C) Castor Material: PP Co-Polymer Core with Soft Grey/Black EVA/TPR/PVC tread on Wheel. (D) Various sized Stems (Mountings) can also be made as per requirements. (E) Castors can be made in any colour combination required.</p>	<p>BENEFITS: Provides sufficient traction. Cost-effective, Squeak-free, Scratch-resist, Ideal for modern floorings. QUALITY TEST: Passed as per International Standards (ANSI, BIFMA, DIN, EN etc.). OEM's are welcome.</p>
13	STUNNER	ST		<p>(A) Serviceable Castor. (B) Static Loading Capacity - 60 kgs per Castor. (C) Wheel Diameter - 50 mm. (D) Castor Material - Self Lubricating Nylon. (E) Riveted Wheels for extra load bearing capacity. (F) Various sized Stems (Mountings) can also be made as per requirements. (G) Castors can be made in any colour required.</p>	<p>BENEFITS: Hassle-free performance for years, Ideal for Carpet & modern floorings. QUALITY TEST: Passed as per International Standards (ANSI, BIFMA, DIN, EN etc.). OEM's are welcome.</p>
14	GLIDE	GL		<p>(A) Static Loading Capacity - 65 kgs per Castor. (B) Wheel Diameter - 50 mm (Heavy Duty). (C) Castor Material - Self Lubricant Nylon. (D) Riveted Wheels for extra load bearing capacity. (E) Various sized Stems (Mountings) can also be made as per requirements. (F) Castors can be made in any colour required.</p>	<p>QUALITY TEST: Passed as per International Standards (ANSI, BIFMA, DIN, EN etc.). OEM's are welcome.</p>
15	CLASSIC	CL		<p>(A) Static Loading Capacity - 50 kgs per Castor. (B) Wheel Diameter - 50 mm. (C) Castor Material - Nylon 6 (Also, available in Virgin PP). (D) Riveted Wheels for extra load bearing capacity. (E) Various sized Stems (Mountings) can also be made as per requirements. (F) Castors can be made in any colour required. (G) Hooded castors with Black or Plated Hub.</p>	<p>QUALITY TEST: Passed as per International Standards (ANSI, BIFMA, DIN, EN etc.). OEM's are welcome.</p>
16	SLEEK	SL		<p>(A) Static Loading Capacity - 50 kgs per Castor. (B) Wheel Diameter - 50 mm. (C) Hub Dia : 30 mm. (D) Castor Material - High Impact Nylon. (E) Unhooded castors with Black or Plated Body. (F) Various sized Stems (Mountings) can also be made as per requirements. (G) Castors can be made in any colour required.</p>	<p>QUALITY TEST: Passed as per International Standards (ANSI, BIFMA, DIN, EN etc.). OEM's are welcome.</p>

17	INTERCEPTOR	IC		<p>LOCKABLE. (A) Static Loading Capacity - 50 kgs per Castor. (B) Wheel Diameter - 50 mm. (C) Hub Dia : 30 mm. (D) Castor Material - High Impact Nylon. (E) Unhooded Lockable Castors with Black or Plated Body. (F) Various sized Stems (Mountings) can also be made as per requirements. (G) Castors can be made in any colour required.</p>	<p>QUALITY TEST: Passed as per International Standards (ANSI, BIFMA, DIN, EN etc.). OEM's are welcome.</p>
----	-------------	----	---	--	--




40 MM WHEEL DIAMETERS:


18	TINY	TY		<p>(A) Static Loading Capacity - 20 kgs per Castor. (B) Wheel Diameter - 40 mm. (C) Castor Material - Nylon 6 (Also, available in Co-Polymer PP on Customers' demand). (D) Available in NY or MS Center Shaft & Adapter. (E) Various sized Stems (Mountings) can also be made as per requirements. (F) Castors can be made in any colour required. (G) Hooded castors with Black or Plated Hub.</p>	<p>QUALITY TEST: Passed as per International Standards (ANSI, BIFMA, DIN, EN etc.). OEM's are welcome.</p>
19	TINY-B	TY-B		<p>LOCKABLE. (A) Static Loading Capacity - 30 kgs per Castor. (B) Wheel Diameter - 40 mm. (C) Lockable Castor, Material - Nylon 6 (Also, available in Co-Polymer PP on Customers' demand). (D) Available in NY or MS Center Shaft & Adapter. (E) Various sized Stems (Mountings) can also be made as per requirements. (F) Castors can be made in any colour required. (G) Hooded castors with Black or Plated Hub.</p>	<p>QUALITY TEST: Passed as per International Standards (ANSI, BIFMA, DIN, EN etc.). OEM's are welcome.</p>
20	SPARKLE	SP		<p>(A) Static Loading Capacity - 20 to 30 kgs per Castor. (B) Wheel Diameter - 40 mm. (C) Castor Material - Nylon 6 with ABS Chrome Plated Cap. (Also, available in PP). (D) Various sized Stems (Mountings) can also be made as per requirements. (E) Castors can be made in any colour required. (F) Specially fitted with Chrome Plated Cap to add rich & elegant look to your furniture. (G) Hooded castors with Black or Plated Hub.</p>	<p>QUALITY TEST: Passed as per International Standards (ANSI, BIFMA, DIN, EN etc.). OEM's are welcome.</p>

21	GP40	GP40		(A) Static Loading Capacity - 40 kgs per Castor. (B) Wheel Diameter - 40 mm. (C) Unhooded Castor, Material - High Impact Nylon Core with Soft PU tread on Wheel. (D) Various sized Stems (Mountings) can also be made as per requirements. (E) Castors can be made in any colour combination required.	BENEFITS: Provides sufficient traction. Squeak-free, Scratch-resist, Ideal for modern floorings. QUALITY TEST: Passed as per International Standards (ANSI, BIFMA, DIN, EN etc.). OEM's are welcome.
22	GP40-LOCK	GP40-LOCK		LOCKABLE. (A) Static Loading Capacity - 40 kgs per Castor. (B) Wheel Diameter - 40 mm. (C) Unhooded lockable Castor, Material - High Impact Nylon Core with Soft PU tread on Wheel. (D) Various sized Stems (Mountings) can also be made as per requirements. (E) Castors can be made in any colour combination required.	BENEFITS: Provides sufficient traction. Squeak-free, Scratch-resist, Ideal for modern floorings. QUALITY TEST: Passed as per International Standards (ANSI, BIFMA, DIN, EN etc.). OEM's are welcome.

30 MM WHEEL DIAMETERS:					
23	GLIB	GB		(A) Static Loading Capacity - 25 kgs per Castor. (B) Wheel Diameter - 30 mm. (C) Castor Material - High Impact Nylon. (D) Unhooded castors with Black or Plated Hub. (E) Various sized Stems (Mountings) can also be made as per requirements. (F) Castors can be made in any colour required.	QUALITY TEST: Passed as per International Standards (ANSI, BIFMA, DIN, EN etc.). OEM's are welcome.
24	GLIB-LOCK	GB-B		LOCKABLE. (A) Static Loading Capacity - 25 kgs per Castor. (B) Wheel Diameter - 30 mm. (C) Castor Material - High Impact Nylon. (D) Unhooded lockable castors with Black or Plated Hub. (E) Various sized Stems (Mountings) can also be made as per requirements. (F) Castors can be made in any colour required.	QUALITY TEST: Passed as per International Standards (ANSI, BIFMA, DIN, EN etc.). OEM's are welcome.


B. STEMS (MOUNTINGS)

SR.NO.	PRODUCT NAME	PRODUCT CODE	I M A G E S	C H A R A C T E R I S T I C S
1	U-CLAMP	UCL		(A) It fixes on 16mm & 19 mm panels. (B) Any size of Clamp can be made.
2	THREADED STEM	THP		(A) 3/8", 5/16", M8, M10 Thread Type. (B) Any size of Stem can be made.
3	PLATE	PLT		(A) 40x40 mm & 28x28 mm Square Plate. (B) Any size of Plate can be made.

4	KING PIN	KGP		(A) 10 mm & 11 mm Push Type in MS. (B) Any size of Stem can be made.
5	NYLON PLASTIC SOCKET	NPS	Image not available	(A) 12.5 mm & 12.8 mm Push Type in NY. (B) Any size of Stem can be made.
6	NYLON PLASTIC SOCKET WITH METAL STEM	NPS-MS	Image not available	(A) 12.5 mm Push Type NY Stem with Metal Insert. (B) Any size of Stem can be made.

NOTE: VARIOUS OTHER STEMS (MOUNTINGS) CAN BE DEVELOPED AS PER CUSTOMERS' REQUIREMENT.

C. CHAIR BASE

SR.NO.	PRODUCT NAME	PRODUCT CODE	I M A G E S	C H A R A C T E R I S T I C S
1	24" CHAIR BASE	CB24		(A) Static Loading Capacity: 700 kgs (B) Raw Material: Co-polymer (PPCP). (C) Quality Test passed as per International Standards. (D) OEM'S ARE WELCOME.

2	26" CHAIR BASE	CB26		<p>(A) Static Loading Capacity: 1250 kgs. (B) Raw Material: 30% Glass reinforced Nylon. (C) Quality Test passed as per International Standards. (D) OEM'S ARE WELCOME.</p>
3	26" HIGH BASE	HB26		<p>(A) Static Loading Capacity: 1250 kgs. (B) Raw Material: 30% Glass reinforced Nylon. (C) Quality Test passed as per International Standards. (D) OEM'S ARE WELCOME.</p>
4	Jumbo (24" & 26")	JB-24/JB-26		<p>(A) Static Loading Capacity: Upto 1300 kg. (B) Raw Material: 30% Glass reinforced Nylon. (C) Quality Test passed as per International Standards. (D) OEM'S ARE WELCOME.</p>